

**IN THE CLAIMS:**

Please amend the claims as set forth below:

1. (Currently Amended) A way predictor comprising:

a decoder that decodes an indication of a first address that is to access a cache for a current cache access during use, the decoder selecting a set responsive to the indication of the first address during use;

a memory coupled to the decoder, wherein the memory outputs a plurality of values from the set in response to the decoder selecting the set during use, wherein each of the plurality of values corresponds to a different way of a plurality of ways of the memory, wherein the cache includes a same number of ways as the memory, and wherein the cache includes a tag memory storing a plurality of tags corresponding to cache lines stored in the cache and a data memory storing the cache lines during use, wherein each value of the plurality of values comprises a plurality of bits, and wherein each value is associated with a different corresponding cache line stored in the cache in a respective way of the plurality of ways, and wherein the different corresponding cache line is stored in the set selected by the decoder, and wherein there is a one-to-one correspondence between the different corresponding cache lines and the ~~of the~~ plurality of values, and the plurality of bits forming a given value of the plurality of values, as a whole, is the value associated with the different cache line, and wherein each bit of the plurality of bits of the given value is formed from a logical combination of two or more virtual address bits from a virtual address that corresponds to the different cache line;

a way prediction generator circuit coupled to receive a first virtual address corresponding to the first address, and wherein the way prediction generator logically combines bits of the first virtual address to generate a

first value during use; and

a circuit coupled to receive the plurality of values and ~~corresponding to the first address~~ [[a]] the first value and the first value comprising a second plurality of bits, wherein the circuit compares the first value to the plurality of values during use, and wherein a match of the first value and a second value stored in a first way of the plurality of ways causes the circuit to predict the first way to be a hit in the cache for the first address for the current access during use, and wherein the circuit outputs a way identifier identifying the first way to the data memory during use, the way identifier used by the data memory to select the first way to output data during use, and wherein the circuit constructs the way identifier based on the comparisons of the first value to the plurality of values during use.

2. (Cancelled)

3. (Previously Presented) The way predictor as recited in claim 1 wherein the circuit, responsive to none of the plurality of values matching the first value in the current cache access, asserts an early miss signal during use, wherein the early miss signal indicates that the first address is a miss in the cache for the current cache access prior to a tag comparison between the first address and the plurality of tags for the current cache access.

4-8. (Cancelled)

9. (Original) The way predictor as recited in claim 1 wherein the indication of the first address comprises at least a portion of the first address.

10. (Previously Presented) The way predictor as recited in claim 1 wherein the indication of the first address comprises two or more address operands used to generate the first address.

11. (Previously Presented) The way predictor as recited in claim 1 wherein, if the first way is an incorrect prediction, the cache replaces a cache line in the first way with a missing cache line corresponding to the first address during use.

12. (Previously Presented) The way predictor as recited in claim 11 wherein, if no way prediction is generated and a cache miss results for the first address, the cache uses a replacement algorithm to select the cache line to be replaced with the missing cache line during use.

13. (Currently Amended) A method comprising:

decoding an indication of a first address that is to access a cache to select a set;

outputting a plurality of values from the set in a memory in response to the set being selected, wherein each of the plurality of values corresponds to a different way of a plurality of ways of the memory, wherein the cache includes a same number of ways as the memory, and wherein the cache includes a tag memory storing a plurality of tags corresponding to cache lines stored in the cache and a data memory storing the cache lines, and wherein each value of the plurality of values comprises a plurality of bits associated with a different corresponding cache line stored in the cache in a respective way of the plurality of ways, and wherein the different corresponding cache line is stored in the set selected in the decoding, and wherein there is a one-to-one correspondence between the different corresponding cache lines and the ~~of the~~ plurality of values, and the plurality of bits forming a given value of the plurality of values, as a whole, is the value associated with the different cache line, and wherein each bit of the plurality of bits of the given value is formed from a logical combination of two or more virtual address bits from a virtual address that corresponds to the different cache line;

receiving a first virtual address corresponding to the first address;

logically combining bits of the first virtual address to generate a first value;

comparing each of the plurality of values to ~~[[a]]~~ the first value ~~corresponding to the first address~~, wherein the first value comprises a second plurality of bits, and wherein a hit in a first way of the cache is indicated for prediction based on a match of the first value and a second value stored in the first way of the memory;

predicting the first way of the plurality of ways to be a hit in the cache for the first address responsive to the first value matching one of the plurality of values; and

constructing a way identifier that identifies the first way to the data memory, the way identifier used by the data memory to select the first way to output data, and wherein the constructing is based on the comparisons of the first value to the plurality of values.

14. (Cancelled)

15. (Previously Presented) The method as recited in claim 13 further comprising, responsive to none of the plurality of values matching the first value in a current cache access, indicating a miss for the current cache access prior to comparing the plurality of tag values to a tag portion of the first address for the current cache access.

16-20. (Cancelled)

21. (Previously Presented) The method as recited in claim 13 further comprising:

detecting that the first way is an incorrect prediction; and

replacing a cache line in the cache in the first way with a missing cache line corresponding to the first address.

22. (Original) The method as recited in claim 21 further comprising, if no way prediction is generated and a cache miss results for the first address, using a replacement algorithm to select the cache line to be replaced with the missing cache line.

23. (Currently Amended) An apparatus comprising:

a way predictor comprising:

a decoder that decodes an indication of a first address that is to access a cache for a current cache access during use, the decoder selecting a set responsive to the indication of the first address during use;

a memory coupled to the decoder, wherein the memory outputs a plurality of values from the set in response to the decoder selecting the set during use, wherein each of the plurality of values corresponds to a different way of a plurality of ways of the memory, wherein the cache includes a same number of ways as the memory, and wherein the cache includes a data cache tag memory storing a plurality of tags corresponding to cache lines stored in the cache and a data cache data memory storing the cache lines during use, wherein each value of the plurality of values comprises a plurality of bits, and wherein each value is associated with a different corresponding cache line stored in the cache in a respective way of the plurality of ways, and wherein the different corresponding cache line is stored in the set selected by the decoder, and wherein there is a one-to-one correspondence between the different

corresponding cache lines and the ~~of the~~ plurality of values, and the plurality of bits forming a given value of the plurality of values, as a whole, is the value associated with the different cache line, and wherein each bit of the plurality of bits of the given value is formed from a logical combination of two or more virtual address bits from a virtual address that corresponds to the different cache line;

a way prediction generator circuit coupled to receive a first virtual address corresponding to the first address, and wherein the way prediction generator logically combines bits of the first virtual address to generate a first value during use; and

a first circuit coupled to receive the plurality of values and ~~[[a]]~~ the first value corresponding to the first address and the first value comprising a second plurality of bits, wherein the first circuit compares the first value to the plurality of values during use, and wherein a match of the first value and a second value stored in a first way of the plurality of ways causes the first circuit to predict the first way to be a hit in the cache for the first address for the current access during use, and wherein the first circuit outputs a way identifier identifying the first way to the data cache data memory during use, the way identifier used by the data cache data memory to select the first way to output data during use, and wherein the first circuit constructs the way identifier based on the comparisons of the first value to the plurality of values during use; and

the data cache data memory coupled to the way predictor, wherein the data cache data memory is arranged into the plurality of ways, and wherein the data cache data memory outputs data from the first way during use, and

wherein the data cache data memory includes a second circuit that reduces power consumption attributable to one or more non-predicted ways of the plurality of ways during use.

24. (Previously Presented) The apparatus as recited in claim 23 further comprising the data cache tag memory outputting a tag from the first way and not outputting tags from the one or more non-predicted ways during use.

25. (Previously Presented) The apparatus as recited in claim 23 wherein the second circuit generates separate wordlines for each of the plurality of ways in the data cache data memory during use, and wherein the second circuit activates a first wordline to the first way and does not activate word lines to the non-predicted ways during use.

26. (Previously Presented) The apparatus as recited in claim 25 wherein the second circuit includes column multiplexor circuitry coupled to the plurality of ways, wherein the column multiplexor circuitry selects the output of the first way as input to a sense amplifier circuit during use, wherein the column multiplexor circuitry is controlled by the predicted first way.

27. (Previously Presented) The apparatus as recited in claim 23 wherein the second circuit includes column multiplexor circuitry coupled to the plurality of ways, wherein the column multiplexor circuitry selects the output of the first way as input to a sense amplifier circuit during use, wherein the column multiplexor circuitry is controlled by the predicted first way.

28. (Previously Presented) The apparatus as recited in claim 23 wherein the second circuit comprises a plurality of sense amplifier circuits, wherein each of the plurality of sense amplifier circuits is coupled to a respective one of the plurality of ways, and wherein each of the plurality of sense amplifier circuits includes an enable input that is controlled by the predicted first way.

29. (Previously Presented) The apparatus as recited in claim 23 further comprising a second level cache, and wherein the circuit detects a miss responsive to the plurality of values and the first value prior to the miss being detected in the cache that corresponds to the data cache data memory during use, and wherein the circuit signals the miss to the second level cache during use, and wherein the second level cache begins an access corresponding to the first address responsive to signal from the circuit during use.